


07-27-00

Attorney Docket No. P2023

**IN THE UNITED STATES PATENT AND TRADEMARK OFFICE**

**CERTIFICATE OF EXPRESS MAILING**

I hereby certify that this paper and the documents and/or fees referred to as attached therein are being deposited with the United States Postal Service on July 26, 2000 in an envelope as "Express Mail Post Office to Addressee" service under 37 CFR § 1.10, Mailing Label Number EL391268733US, addressed to Assistant Commissioner of Patents, Washington, DC 20231.

  
Steve S. Cha

**UTILITY PATENT APPLICATION TRANSMITTAL (37 CFR § 1.53(b))**

Assistant Commissioner for Patents  
Box Patent Application  
Washington, D.C. 20231

Transmitted herewith for filing is the patent application under 37 CFR § 1.53(b) in the name of inventor(s) of:

Choon-Keun Song

For: METHOD FOR PROCESSING A LARGE AMOUNT OF INTR-CALLS IN A REMOTE CONTROL SYSTEM OF A FULL ELECTRONIC TELEPHONE

Enclosed are:

Application Elements:

- ☒ 2 copies each of 5\_ sheets of informal drawing(s).
- ☒ Assignment of the invention to: SAMSUNG ELECTRONIC CO., LTD.
- ☒ Specification, Claims, and Abstract: Nr. of sheets: 12
- ☒ A copy of combined declaration and power of attorney

Accompanying Application Parts:

- ☒ A check\* 1828 in the amount of \$690.00 for filing fee
- ☒ A Return Receipt Postcard
- ☒ Assignment and Assignment Recordation Cover Sheet (recording fee of \$40.00 enclosed)

- ☒ Claim of priority under 35 U.S.C. §119 and a copy of certified Korean Patent Application.
- ☐ Information disclosure statements: Nr. of sheets: 3
- ☐ Preliminary Amendment
- ☐ Small Entity Statement(s)
- ☐ Other:

The filing fee has been calculated as shown below (37 CFR §1.16):

For:	No. Filed	No.Extra	Rate(Small Entity)	Fee(Small Entity)
Basic Fee	20 claims			\$ 690.00
Total Claims	3 claims – 20 =	0	\$18(\$9)/claim	\$ 0.00
Independent Claims	1 claim – 3 =	0	\$78(39)/claim	\$ 0.00
Multiple Dep.Claims			\$130(65)/claim	\$ 0.00
Total Filing Fee				\$ 690.00


General Authorization for Petition for Extension of Time (37 CFR §1.136)

Applicant hereby make and generally authorize any Petitions for Extensions of Time as may be needed for any subsequent filings.

Should the enclosed check become lost or detached from the file, Assistant Commissioner is authorized to charge our Deposit Account No. 50-1005 and advise the undersigned attorney accordingly. Also, should the enclosed check be deemed to be deficient or excessive in payment, the Commissioner is authorized to charge or credit our deposit account and notify the undersigned attorney of any such transaction.

In view of the above, it is respectfully requested that this application be accorded a filing date pursuant to 37 C.F.R. §1.53(b).

Mailed: July 26, 2000

  
 Steve S. Cha, Registration No. 44,069  
 Attorney for Applicant(s)

Please address all Correspondence to:

**Steve S. Cha, Esq.**  
 67 Wall Street #2211  
 New York, NY 10005-3198  
 Tel: (212) 968-7101  
 Fax: (212) 968-7105

**Customer No:022491**



**22491**

PATENT TRADEMARK OFFICE

**METHOD FOR PROCESSING A LARGE NUMBER OF INTRA-CALLS IN A  
REMOTE CONTROL SYSTEM OF A FULL ELECTRONIC TELEPHONE  
EXCHANGE SYSTEM**

**CLAIM OF PRIORITY**

This application makes reference to, incorporates the same herein, and claims all benefits accruing under 35 U.S.C. Section 119 from an application for METHOD FOR PROCESSING A GREAT AMOUNT OF INTRA-CALLS IN A REMOTE CONTROL SYSTEM OF A FULL ELECTRONIC TELEPHONE EXCHANGE SYSTEM filed earlier in the Korean Industrial Property Office on July 26, 1999 and there duly assigned Serial No. 30440/1999.

**BACKGROUND OF THE INVENTION**

**1. Field of the Invention**

The present invention relates to a remote control system of a full electronic telephone (PSDN/PSTN) exchange system. More particularly, the present invention relates to a method for processing a large number of intra-calls in the remote control system regardless of the limitation of the capacity of an intra-junction.

## 2. Description of the related art

The conventional remote control system of a full electronic telephone switching system employs a non-blocking method for processing intra-calls (internal calls). Yet, the number of intra-calls that can be processed within the full electronic telephone exchanger is limited according to the intra-junction capacity of the time switch block.

In the conventional TDX-10 and TDX-10A system utilizing a time division multiple access (TDMA) mode, the capacity of the intra-junction is limited to less than a 1K time slot when processing the intra-calls in a non-blocking remote control system. Hence, the remote control system may not process a large number of intra-calls in non-blocking way due to both the traffic limitation and the capacity limitation of the intra-junction. In addition, it is not possible to equip the intra-junction with a large capacity due to the incompatibility with the host system, thus requiring a function for collecting lines to process a large amount of the intra-calls. Consequently, the limitation of the calls according to the capacity of the intra-junction imposes problems in processing the intra-calls in a remote control system when dealing with a large capacity greater or equal to a 4K-time slot.

## SUMMARY OF THE INVENTION

It is an object of the present invention to provide a method for processing a large amount of the intra-calls in the remote control system of a full electronic exchange system, which enables the remote control system to employ a larger capacity to be used in connection with the host link path.

It is another object of the present invention to provide a method for processing a large amount of the intra-calls in the remote control system of a full electronic exchange system, which enables the remote control system to employ both the time slot for the intra-junctor and the 4K time slot for the host link path.

According to an aspect of the present invention, a method for processing a great amount of intra-calls in the remote control system of a full electronic exchange system, whose time switch block is provided with a voice memory device and a control memory device to switch the PCM (Pulse Code Modulation) data to the intra-direction, and with a call pass controller to transfer the PCM data to the host system or to loop the PCM data to the intra-direction, the method comprising the steps of writing call direction data for designating the intra-call direction into the data region of the control memory device to switch the PCM data sequentially stored in the voice memory device to the intra-direction, and looping the entire channels to the intra-direction to switch the PCM data from the time switch block to the intra-direction if the call direction data designates the intra-call direction

according to the treatment of the great amount of intra-calls.

The present invention will now be described more specifically with reference to the drawings attached only by way of example.

5

### **BRIEF DESCRIPTION OF THE ATTACHED DRAWINGS**

10

Fig. 1 is a block diagram for illustrating the structure of the time switch of the remote control system of a conventional full electronic exchange system;

Fig. 2 is a block diagram for illustrating the structure of the time switch control and maintenance adapter (TSCMA) according to the present invention;

15

Figs. 3A and 3B are examples of the write format of a control memory device; and.

Fig. 4 is a schematic diagram for illustrating the process of treating a great amount of the intra-calls by the remote control system according to the present invention.

20

## DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

In the following description, for purposes of explanation rather than limitation, specific details are set forth such as the particular architecture, interfaces, techniques, etc., in order to provide a thorough understanding of the present invention. However, it will be apparent to those skilled in the art that the present invention may be practiced in other embodiments that depart from these specific details. For the purpose of clarity, detailed descriptions of well-known devices, circuits, and methods are omitted so as not to obscure the description of the present invention with unnecessary detail.

With reference to Fig. 1, the time switch and link (TSL) circuit of the remote control system of a conventional full electronic exchange system comprises a sub-highway multiplexer & demultiplexer adapter (SMDXA) 100 for multiplexing the data received through the sub-highway SHW0~63 and the information in the form of PCM coded data is transferred to a time switch control and maintenance adapter (TSCMA) 200. Similarly, the SMDXA 100 demultiplexes the PCM data received from the TSCMA 200 and transfers the demultiplexed PCM data to the sub-highway SHW0~63.

The TSCMA 200 receives clock signals from a maximum of 4 local transfer and receiver interface adapters (LTRIAs) 300 and two pairs of signals in the level of low voltage differential signaling (LVDS) from a doubled remote network synchronization equipment (RNSE) when installed in a remote access switching module (RASM). Namely,

one pair from the network synchronization A-side of the RASM and the other pair from the B-side are received from the supplemental connector of a time switch back panel adapter (TSBPA) through a 3\*3 clock-cable. Since the fourfold link clock signal and twofold network synchronization clock signal may have different phases, a selected reference clock signal is transmitted to both SMDXA 100 and LTRIA 300 for the synchronization clock signal of the TSL block.

The LTRIA 300 receives the reference clock signal and reproduces the synchronization clock signal, transferring the FP2 and CP2 signals required for selecting the internal synchronization clock signal of the TSL in the LVDS level and the valid signal in the TTL level to the TSCMA 200. A telephony device control master (TDCMA) 400 is provided as a lower processor to control the devices.

Fig. 2 illustrates the structure of the TSCMA according to the present invention. It includes a SMDXA Rx combiner 201 to combine the PCM data received from the SMDXA 100 of Fig. 1, treating a 2K time slot for each SMDXA and at maximum a 8K time slot when having four SMDXAs. The signal line receives the PCM data in the LVDS level.

A clock reception/distribution unit 203 receives the FP2 and CP2 signals inputted from the LTRIA 300 to the TSCMA 200 to distribute the synchronization pulses and clock signals selected in the same way for each doubled board among the boards. An RS-485



device 205 receives the signals from the TDCMA 400 and interfaces through a DS-BUS I/F 209.

An SMDXA Tx combiner 207 switches the PCM data of the TSCMA 200 to the SMDXA 100, treating a 2K time slot for each SMDXA, and at maximum 8K time slot for four SMDXAs. The PCM data line transmits data in the LVDS level.

A Tx control memory combiner 211 comprises a voice memory device and control memory device serve to switch 16.384 Mbps voice data of 2K time slot inputted from the SMDXA 100 at maximum 8K time slot in the inter-direction (S-Switch or Host system) and intra-direction. Here, the switched PCM data may be transferred to the inter-direction (S-Switch), or looped to an Rx control memory combiner 213. In addition, the 2K time slot PCM data in the intra-direction is demultiplexed in the outside of the memory module with the even 1K for the intra-looping and the odd 1K to the additional services.

The Rx control memory combiner 213 switches the 2K time slot PCM data inputted from the LTRIA 300, and the 2K time slot PCM data formed through the inter-path. The LTRIA 300 may contain at maximum 4K-time slot, and transmit the switched PCM data at maximum 8K-time slot to the SMDXA 100 in the LVDS level. A time slot-rearranging unit 215 rearranges the time slot of the intra-switched PCM data.

A call pass controller Sel 219 is a looping processor to the host system, making the

inter-call service of the host system not require the call pass through the LTRIA 300. Hence, the entire channels are looped and used<sup>2</sup> for the call pass under S/W control; a maximum of 4K-time slot may be used.

5           A LTRIA Tx combiner 221 transfers the PCM data switched in the TSCMA 200 to the LTRIA 300, treating 2K time slot for each LTRIA, and at maximum 4K time slot for two LTRIAs. The PCM data is transmitted in the LVDS level. An additional service combiner 227 serves to process recorded voice guides, conference calls, DTMF, and R2 signals, and also transmits the reference clock signals MCLK and MFS to the TSCMA 200.

10          An LTRIA Rx combiner 231 serves to combine the PCM data received from the LTRIA 300, treating 2K-time slot for each LTRIA. The PCM data is received in the LVDS level.

Hereinafter is described the write format of the control memory device in reference to Figs. 3A and 3B. In order to control the PCM data inputted from the TSL block, the control memory should be written by the lower processor. Thus, the control memory device is written with the format, as shown in Figs. 3A and 3B, in order to switch the data sequentially written into the voice memory device to a desired direction. If the inter-directional data region Bit15(LS) of the control memory device is set to "0" while processing a large amount of the intra-calls, the inter-call is written into the Rx-direction voice memory becoming the intra-call instead of the inter-call of the S-Switch direction, so that 4K inter-call may be used as the intra-call by employing the data region Bit 15 when switching the 2K and 4K regions of the intra-call.

The data regions of the control memory device are divided into the output data region as shown in Fig. 3A and the input data region as shown in Fig. 3B, written with data for selecting a memory and address for each input/output data, kind of the input/output memory, capacity of the input/output time slot, number of the sub-highway input/output through the intra-junction, and data for selecting the channel number input/output through the intra-junction. In addition, the output data region is written with data for E/O (Even/Odd) data, while the input data region is written with the data for designating the inter- and intra-call, and with the data for inserting and retrieving the cut-off-cut-bits by the TSCMA 200.

Referring to Fig. 4, a large amount of intra-calls are looped by writing data for designating the intra-calls into the data region of the control memory device, as shown in Fig. 3. As described above, this is achieved by providing the time switch block of the full electronic exchange system with a voice memory device and a control memory device to switch the PCM data to the intra-direction and with a call pass controller to transfer to the host system or loop to the intra-direction the PCM data. Then, the data region of the control memory is written with the call direction data for designating the intra-call direction to switch the PCM data sequentially stored in the voice memory device to the intra-direction, so that the entire channels may be looped to the intra-direction to switch the PCM data from the time switch block to the intra-direction.

Thus, the remote control system of the full electronic exchange system may

process a large amount of intra-calls by employing the host link path for processing them under a software control without any additional board and hardware, regardless of the capacity of the intra-junctor. While the present invention has been described in connection with specific embodiments accompanied by the attached drawings, it will be readily  
5   apparent to those skilled in the art that various changes and modifications may be made thereto without departing the gist of the present invention.

**WHAT IS CLAIMED IS:**

1. A method for processing a large amount of intra-calls in a remote control system of a full electronic exchange system of the type having a time switch block with a voice memory device and a control memory device to switch the Pulse Code Modulation (PCM) data to the intra-direction, and a call pass controller for transferring said PCM data to a host system and for looping said PCM data to an intra-direction, comprising the steps of:

writing call direction data for designating said intra-call direction into the data region of said control memory device to switch said PCM data sequentially stored in said voice memory device to said intra-direction; and,

looping entire channels to said intra-direction to switch said PCM data from said time switch block to said intra-direction if said call direction data designates said intra-call direction based on the amount of said intra-calls.

2. The method as defined in Claim 1, wherein the step of writing call direction data further includes the step of writing data to select the memory and address for each data input/output.

3. The method as defined in Claim 2, wherein the step of writing call direction data further includes the step of writing data to select the kind of input/output memory, capacity of the input/output time slot, number of the sub-highway inputted/outputted through the intra-junction, and number of the channel inputted/outputted through said intra-junction.

**ABSTRACT**

A method for processing a great amount of intra-calls in the remote control system of a full electronic exchange system, whose time switch block is provided with a voice memory device and a control memory device to switch the PCM data to the intra-direction, and with a call pass controller to transfer to the host system or loop to the intra-direction the PCM data, comprises the steps of writing call direction data for designating the intra-call direction into the data region of the control memory device to switch the PCM data sequentially stored in the voice memory device to the intra-direction, and looping the entire channels to the intra-direction to switch the PCM data from the time switch block to the intra-direction if the call direction data designates the intra-call direction according to the treatment of the great amount of the intra-calls.




FIG. 1

FIG. 2






FIG. 3A

[CONTROL MEMORY ADDRESS]

MODE															4			
15	14	13	12	11	10	9	8	7	6	5	4	3	2	1	0			
CMS2CMS1CMS0				OUTPUT CHANNEL				OUTPUT SHW				E/O			0			
0	CMSEL			2K TIME SLOT														
CMS2	CMS1	CMS0	CMSEL			CONTROL MEMORY OPERATION												
0	0	0	0			TCM0												
0	0	1	1			TCM1												
0	1	0	2			TCM2												
0	1	1	3			RCM0												
1	0	0	4			RCM1												
1	0	1	5			RCM2												
1	1	0	6			RCM3												
OUTPUT TS			2K-TIME SLOT OUTPUTTED TO SSL															
OUTPUT SHW			NUMBER OF 1K SUB-HIGHWAY OUTPUTTED TO INTRA-JUNCTOR															
OUTPUT CH			NUMBER OF 1K CHANNEL OUTPUTTED TO INTRA-JUNCTOR															
E/O			EVEN 1K/ODD 1K TIME SLOT,EVEN;0, ADD;1															

FIG. 3B

[CONTROL MEMORY DATA]

MODE															4			
15	14	13	12	11	10	9	8	7	6	5	4	3	2	1	0	E/O		
CMS2CMS1CMS0				INPUT CH							INPUT SHW							
LS	IB	SMSSEL			INPUT TS													

SMS2	SMS1	SMS0	SMSSEL	SPEECH MEMORY OPERATION	
0	0	0	0	TCM(0~2)	RCM(0~3)
0	0	1	1	TSM0(n)	RSM0(n)
0	1	0	2	TSM1(n)	RSM1(n)
0	1	1	3	TSM2(n)	RSM2(n)
1	1	0	6	TSM3(n)	
1	0	0	4	TSMJ(n)	
1	0	1	5	LSMJ0(2)	
				LSMJ1(2)	
INPUT TS				2K TIME SLOT INPUTTED FROM SSL	
INPUT SHW				NUMBER OF 1K SUB-HIGHWAY INPUTTED FROM IJ OR FIJ	
INPUT CH				NUMBER OF 1K CHANNEL INPUTTED FROM IJ OR FIJ	
LS				INTER CALL LOOP 1:INTER, 0:LOOP	
IB				INSERTING AND RETRIEVING CUT-OFF-CUT-BITS BY TSCMA	




FIG. 4

**IN THE UNITED STATES PATENT AND TRADEMARK OFFICE**

In re application of: Choon-Keun Song

Serial No: *Not yet assigned.*

Examiner: *Not yet assigned.*

Filed: July 26, 2000

Group: *Not yet assigned.*

For: METHOD FOR PROCESSING A LARGE AMOUNT OF INTR-CALLS IN A  
REMOTE CONTROL SYSTEM OF A FULL ELECTRONIC TELEPHONE

**TRANSMITTAL OF DECLARATION**

Assistant Commissioner for Patents  
Washington, DC 20231

Sir:

This transmittal accompanies a fax copy of Declaration with the signature by the inventors, for the above-captioned application. A substitute Declaration with the inventors' signature will be filed upon receipt of the Serial No. for the above-captioned application.

Respectfully submitted,



Steve S. Cha  
Attorney for the Applicant  
Registration No.: 44,069

67 Wall Street #2211  
New York, NY 10005-3198  
(212) 968-7101

Date: July 26, 2000

009220 "CHS2350

PTO/SB/02B

Customer No.:022491

Docket No.:

**DECLARATION AND POWER OF ATTORNEY**

As a below named inventor (s), I hereby declare that:

My residence, post office address and citizenship are as stated below next to my name.

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled:

METHOD FOR PROCESSING A LARGE NUMBER OF INTRA-CALLS IN A  
REMOTE CONTROL SYSTEM OF A FULL ELECTRONIC TELEPHONE

,the specification of which is attached hereto unless the following box is checked:

☐ was filed on \_\_\_\_\_ as United States Application Number or PCT International Application  
Number \_\_\_\_\_ and was amended on \_\_\_\_\_ (if applicable).

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose information which is material to patentability as defined in Title 37, Code of Federal Regulation, § 1.56.

I hereby claim foreign priority benefits under Title 35, United States Code, § 119 of any foreign application(s) for patent or inventor's certificate listed below and have also identified below any foreign application for patent or inventor's certificate having a filing date before that of the application on which priority is claimed.

Prior Foreign Application(s)

999-30440  
(Number)

Republic of Korea  
(Country)

26/07/1999  
(Day/Month/Year Filed)

Priority Claimed  
☒ Yes ☐ No

\_\_\_\_\_  
(Number)

\_\_\_\_\_  
(Country)

\_\_\_\_\_  
(Day/Month/Year Filed)

☐ Yes ☐ No

I hereby claim the benefit under Title 35, United States Code, § 120 of any United States application(s) listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States application in the manner provided by the first paragraph of the Title 35, United States Code, § 112, I acknowledge the duty to disclose information which is material to patentability as defined in Title 37, Code of Federal Regulation, § 1.56 which occurred between the filing date of the prior application and the national or PCT international filing date of this application.

\_\_\_\_\_  
(Application Number)

\_\_\_\_\_  
(Filing Date)

\_\_\_\_\_  
(Status - patented, pending, abandoned)

\_\_\_\_\_  
(Application Number)

\_\_\_\_\_  
(Filing Date)

\_\_\_\_\_  
(Status - patented, pending, abandoned)

**POWER OF ATTORNEY:** I hereby appoint the following attorney(s) and/or agent(s) to prosecute this application and to transact all business in the Patent and Trademark Office connected therewith: Steve S. Cho, Registration No. 44,069; Howard S. Reiter, Registration No. 30,384.

Address all correspondence to: Steve S. Cho, Esq.  
67 Wall Street #2411  
New York, NY 10005-3188  
(212)968-7101



22491

PATENT TRADEMARK OFFICE

I (we) hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

Full name of sole or first inventor: Choon-Kaun SONG  
Residence Address: Sokchon-dong, 101-8 Sangpa-gu, Seoul, Korea

Post office address: Same as above  
Citizenship: Republic of Korea

Date: July 26, 2000  
Signature:

Full name of second inventor:  
Residence Address:

Post office address: Same as above  
Citizenship: Republic of Korea

Date: \_\_\_\_\_  
Signature: \_\_\_\_\_


Full name of third inventor:  
Residence Address:

Post office address:  
Citizenship:

Date: \_\_\_\_\_  
Signature: \_\_\_\_\_

009220" 84652960

United States Patent & Trademark Office  
Office of Initial Patent Examination -- Scanning Division



Application deficiencies were found during scanning:

☐ Page(s) \_\_\_\_\_ of \_\_\_\_\_ were not present  
for scanning. (Document title)

☐ Page(s) \_\_\_\_\_ of \_\_\_\_\_ were not present  
for scanning. (Document title)

☒ Scanned copy is best available. *Declaration*